

AL-DUQM INDUSTRIAL MASTERPLAN INVESTOR DESIGN GUIDELINES

JANUARY 2017



PREAMBLE	08
PREFACE	09
PURPOSE	09
HOW, WHY & WHO	09
DOCUMENT STRUCTURE	09

1.INTRODUCTION	10
DUQM INDUSTRIAL PROJECT	11
PROJECT DESCRIPTION	12
DUQM SPECIAL ECONOMIC ZONE AUTHORITY	13
SEZAD VISION	13
SEZAD	13
DUQM INDUSTRIAL IDENTITY	14
DEVELOPMENT CONTROL REGULATIONS INTENT	14
DISCLAIMER	14
DEVELOPMENT CONTROL REGULATIONS INTENT DISCLAIMER	14

2.DUQM MASTERPLAN	15
LANDUSE PLAN	16
DUQM INDUSTRIAL MASTERPLAN	17
LANDUSE BREAKDOWN	17

3.LIGHT INDUSTRY GUIDELINES	18
OVERVIEW	19
DEFINITION	19
PERMITTED USES	20
LIGHT INDUSTRY AREA COMPONENTS	20
LAND USE PLAN	21
DEVELOPMENT STATISTICS	22
DESIGN GUIDELINES	23
PLOT ENVELOPE	23
ACCESS AND CIRCULATION	23
SETBACKS	24
PLOT COVERAGE	27
FAR (FLOOR AREA RATIO)	28
BUILDING HEIGHT	29
PLOT SUBDIVISION / AMALGAMATION	30
PLOT AMALGAMATION	30
PLOT SUBDIVISION	30
PARKING REQUIREMENTS	31
LOADING/UNLOADING	33
BOUNDARY WALLS	34
LANDSCAPING	35
STORMWATER MANAGEMENT AND DRAINAGE	35

CONTENT



4.MEDIUM INDUSTRY GUIDELINES	36
OVERVIEW	37
DEFINITION	37
PERMITTED USES	38
LAND USE PLAN	39
DEVELOPMENT STATISTICS	40
DESIGN GUIDELINES	41
PLOT ENVELOPE	41
ACCESS AND CIRCULATION	41
SETBACKS	42
PLOT COVERAGE	45
FLOOR AREA RATIO (FAR)	46
BUILDING HEIGHT	47
PLOT SUBDIVISION/AMALGAMATION	48
PLOT AMALGAMATION	48
PLOT SUBDIVISION	48
PARKING REQUIREMENTS	49
LOADING/UNLOADING	51
BOUNDARY WALLS	52
LANDSCAPING	53
STORMWATER MANAGEMENT AND DRAINAGE	53



5.HEAVY INDUSTRY GUIDELINES	54
OVERVIEW	55
DEFINITION	55
PERMITTED USES	56
LAND USE PLAN	57
HEAVY INDUSTRY AREA COMPONENTS	57
DEVELOPMENT STATISTICS	58
DESIGN GUIDELINES	59
PLOT ENVELOPE	59
ACCESS AND CIRCULATION	59
SETBACKS	60
PLOT COVERAGE	63
FAR (FLOOR AREA RATIO)	64
BUILDING HEIGHT	65
PLOT SUBDIVISION / AMALGAMATION	66
PLOT AMALGAMATION	66
PLOT SUBDIVISION	66
PARKING REQUIREMENTS	67
LOADING/UNLOADING	69
BOUNDARY WALLS	70
LANDSCAPING	71
STORMWATER MANAGEMENT AND DRAINAGE	71

CONTENT

6. RENEWABLE ENERGY INDUSTRY GUIDELINES	72
OVERVIEW	73
DEFINITION	73
PERMITTED USES	74
RENEWABLE ENERGY INDUSTRY AREA COMPONENTS	74
LAND USE PLAN	75
DEVELOPMENT STATISTICS	76
DESIGN GUIDELINES	77
PLOT ENVELOPE	77
ACCESS AND CIRCULATION	77
BUILDING HEIGHTS	78
SETBACKS	79
PLOT COVERAGE	83
FAR (FLOOR AREA RATIO)	83
PLOT SUBDIVISION / AMALGAMATION	84
PLOT AMALGAMATION	84
PLOT SUBDIVISION	84
PARKING REQUIREMENTS	85
BOUNDARY WALLS	87
LANDSCAPING	88
STORMWATER MANAGEMENT AND DRAINAGE	88
LANDSCAPE, COMMUNITY AND SAFETY CONSIDERATIONS	89
	89

7. ARCHITECTURAL GUIDELINES	90
GENERAL ARCHITECTURAL GUIDELINES	91
MASSING	92
ORIENTATION	93
MATERIALS	95
COLORS	96
SCREENING	96
ROOFS	98
SHADING ELEMENTS	97
LOADING/UNLOADING	98
SUSTAINABILITY MEASURES	99

8. INFRASTRUCTURE GUIDELINES	100
UTILITY SERVICES	101
SITE DRAINAGE AND RUNOFF	101
SITE POWER	102
SITE PORTABLE WATER SUPPLY	103
SITE SEWERAGE	104
SITE TELECOMMUNICATIONS	105

CONTENT



GLOSSARY

Access Drive:	ve: That portion of a vehicular use area that provides vehicular access from the public street to more than one dwelling unit or more than one non-residential building.		Any sign containing electrical wiring, lighting signs illuminated by a detached exterior lighting by a detached exterior light	
Accessory Building or	A building or structure that is subordinate in area, extent and purpose to the principal use and	Facade	The exterior plane or "face" of a building.	
Structure:	building on the lot and that is customarily used or occupied in conjunction with a permitted	FAR	An abbreviation for "floor area ratio."	
Accessory Parking:	Accessory Parking: Parking provided to comply with minimum off-street parking requirements and non-required parking that is provided exclusively to serve occupants and visitors to a particular use, rather than the public at-large. See "non-accessory parking,"		A sign made of fabric or other similar non-r edge or supported or anchored at only two metres as long as any other dimension, it is classified and regulated as a banner re	
Accessory Use	A use that is subordinate in area, extent and purpose to the principal use and that is customarily found in conjunction with a permitted principal use.		also "banner". Any sign or portion of a sign that contains a	
Awning	A roof-like structure of fabric or similar non-rigid material attached to a rigid frame that is supported completely or partially by either an exterior building wall or wall exterior to an individual tenant space.	Flashing Sign	changes light intensity in sudden transitory contain or use strobe lights, or rotating light designed to merely to attract attention rathe	
Awning Sign	A sign incorporated into or attached to an awning.		signs that do not comply with applicable sta	
Banner or Banner Sign	A sign made of fabric or other similar non-rigid material with no enclosing framework or electrical components that is supported or anchored on two or more edges or at all four corners. Banners also include non-rigid signs anchored along one edge, or two corners, with weights installed that reduce the reaction of the sign to wind. See also "flag."		The ratio of the gross floor area of all princi- which such buildings are located. Floor area by the gross plot area. Standards for floor a maximum permitted.	
	The portion of any structure whose height measured from the floor to the underside of ceiling	Free Standing Sign	A sign on a frame, pole, or other support st	
Basement	ment joists is located more than 50% below grade. Basement floor area does not count towards Floor Area Ratio (FAR).		That property line that abuts or is along an public street exists, is along a public way.	
Building:	Any structure that is permanently affixed to the land and built for the support, shelter, or enclosure of persons, animals, channels, or movable property of any kind.	Grade	The curb level adjacent to the front property measured along exterior building walls of the	
Building Height	The dimension from grade to the highest point of the roof or parapet of a building, excluding roof top mechanical equipment, access stair enclosures, and rooftop shading devices.		Gross floor area, for the purpose of calculat	
Bulk	The general term used to refer to the size of a building or the building features allowed on a plot. Provisions that control bulk include the following: plot area, setbacks, open space, floor area, floor area ratio, building coverage, and building height.	Gross Floor Area	horizontal areas of several floors of the buil floor area shall include elevator and stairwe equipment except equipment open or enclo mezzanines: enclosed porches: and floor ar	
Canopy	A roof like structure of a permanent nature that projects from the wall of a building and overhangs the public way.		accessory parking and exterior balconies ar	
	Any sign that, through the use of moving structural elements, sequential lights, lighting	Gross Plot Area	The entire land area within the boundaries	
Changing-image Sign	mage Sign elements, or other automated method, results in movement, the appearance of movement or change of sign image or message. Changing-image signs do not include otherwise static signs where illumination is turned off and back on not more than once every 24 hours. Incidental Sign		A sign that contains no commercial messag or other information for the convenience of t rooms, address numbers, hours of operation telephone, etc. Also included are signs on r	
Commercial Establishment	A business in which, the ownership, management and physical location are separate and distinct from those of any other place of business located on the same zoning plot, as partly evidenced by maintaining separate and distinct doors and access points.		pedestrians or vehicular traffic, such as "ent	
Commercial Message or Commercial Message Sign	Any sign, wording, logo or other representation that, directly or indirectly, names, advertises or calls attention to a business, product, service or other commercial activity.	Individual Letter Sign	The background of an individual letter sign another opaque, non-illuminated surface.	
Density	The general term used to refer to the number of building units allowed per unit of land area. It is controlled in these regulations by the maximum number of building units allowed on a lot and implies a number of building units per acre or hectare	Land Leasee Landscaped Area	The investor of land from SEZAD which see Substantially covered with turf, ground cove Meter (30m = 30 meters). (See also She	
Drive-Thru Facility	Any service window, automated device or other facility that provides goods or services to individuals in motor vehicles.		1	
Driveway	That portion of a vehicular use area that provides vehicular access from the public street to a single dwelling unit or factory building.			

g or other electrical components, but not including ht source.

igid material supported or anchored along only one corners. If any dimension of a flag is more than 3

gardless of how it is anchored or supported. See

an intermittent or flashing light source or that bursts. Example of flashing signs include signs that ts; signs with blinking or flashing features that are er than convey a message; and changing-image andards.

ipal buildings to the total area of the plot upon a ratio is calculated by dividing the gross floor area area ratio in these provisions are stated as the

tructure that is not attached to any building.

existing or dedicated public street, or when no

y line or the mean elevation of the finished lot, as ne principal building, whichever is higher.

ting floor area ratio, is defined as the gross lding measured from the exterior walls. Gross ells at each floor; floor space used for mechanical osed, located on the roof;; interior balconies or rea devoted to accessory uses. Below grade nd/or porches are excluded from gross floor area."

of a plot.

ge and that is exclusively used to convey directions the public. Included are signs designating rest on, entrances to buildings, help wanted, public private property designed to guide or direct trance" and "exit" signs.

sting of raised individual letters, script or symbols. is either the exterior building wall surface or

eks to develop the land for Industrial use purposes.

er, shrubs, trees or other living plant material. m: elterbelt).

GLOSSARY

Marquee	A roof-like structure of a permanent nature that projects from the wall of a building and overhangs the public way.		
Marquee Sign	A sign incorporated into or attached to a marquee or permanent canopy.		
Motor Vehicle	cle Any passenger vehicle, truck, truck-trailer, trailer or semi-trailer propelled or drawn by mechanical power.		
Non-Accessory Parking	Parking spaces (and the drive aisles and circulation area associated with such parking spaces) that are provided to serve the general public rather than being reserved exclusively for occupants of and visitors to a particular use (e.g., public parking garages).		
Off Premise Sign	A sign that directs attention to a business, commodity, service, or entertainment conducted, sold, or offered elsewhere than upon the plot upon which it is located or to which it is affixed.		
On-Premise Sign	-Premise Sign A sign that directs attention to a business or profession conducted or to a commodity, service, or entertainment sold or offered upon the premises where the sign is located.		
Ornamental Fencing	A decorative fence, including wrought iron or fencing that gives the appearance of wrought- iron fencing, but expressly excluding chain-link, barbed wire and similar non-decorative fences.		
Painted Wall Sign A sign applied to a building wall with paint or a thin layer of vinyl, paper or similar material adhered directly to the building surface and that has no sign structure.		Sign	
Permanent Sign	Any sign not classified as a temporary sign.		
Permitted Use	A use permitted by-right in the subject district in accordance with the applicable use regulations of this document.		
Iot CoverageThe area of a plot covered by principal and accessory buildings, as measured along the exterior building wall at ground level, and including all building projections other than those expressly allowed encroaching into required setback areas.		Story	
Podium	The portion of a building encompassing the ground floor or the ground and several additional floors or mezzanine serving as a base for a tower above.		
Portable Sign Any sign not permanently attached to the ground or other permanent structure or a sign designed to be transported, including, but not limited to, signs designed to be transported by means of wheels and signs made as A-frames or T-frames.		Stree Temp	
A building or combination of buildings of chief importance or function on a lot. In general, the principal use is carried out in a principal building. The difference between a principal building and an accessory building or structure is determined by comparing the size, placement, similarity of design, use of		Use	
Principal Use	An activity or combination of activities of chief importance on the lot. One of the main purposes for which the land, buildings or structures are intended, designed, or ordinarily used.	Vehic	
Product Display Window	An illuminated window display area in which products and goods are displayed to pedestrians but do not generally allow visibility into the interior of the building.	Video	
Projecting Sign	A sign attached to and projecting out from a building face or wall, generally at right angles to the building. Projecting signs include signs that are totally in the right-of-way, partially in the right-of-way, or fully on private property.	Wall S	
Public Open Space	Any publicly-owned open area, including, but not limited to parks, playgrounds, beaches, waterways, parkways and streets.	Windo	
Public Way	Any sidewalk, pedestrian path or trail, street, alley, highway, or other public thoroughfare.		

Roof Line	The peak of a roof or top edge of a parape
Roof Sign	A sign or any portion of a sign that is erect roof line of any building whether the princip other structural element of the building.
Satellite Dish Antenna	A device designed or used for the reception communication signal broadcast or, relayed bar configured structure in the shape of a s
Setback	An open, unobstructed area that is required furthermost projection of a structure to the
Shelterbelt	A major landscape strip of land dedicated t across the Duqm Industrial area.
Special Economic Zone Authority Duqm (SEZAD)	The authority appointed by the government Industrial City.
Sign	Materials placed or constructed, or light pro and (2) is used to inform or attract the atter materials or lights meeting the definition of referred to as signs, placards, A-boards, pro or projected slides, images or holograms. V "off -premise," the term "sign" refers to all s
Story	That portion of a building included between floor next above, or if there is no floor above above. A basement or below-grade floor w of the clear floor height is above grade.
Street	Any public road, communal street, private s that provides the pincipal frontage to a dwe battleaxe lot.
Street Frontage	Any portion of a lot that abuts a street (also
Temporary Sign	A sign that is designed to be used only ten structure or permanently installed in the gro
Use	The purpose or activity for which the land, intended, or for which it is occupied or mai term "use" means principal use.
Vehicular Access Point	Any area of the plot not located within any is devoted to a use by or for motor vehicles storage of automobiles, trucks or other veh repair shops; loading areas; service areas
Video Display Sign	A sign capable of displaying full-motion image
Wall Sign	A single-faced sign attached flush to a buil projected onto a building or other structure to sign structures.
Window Display Sign	A single-faced sign attached flush to a pro- surface.

et, whichever is higher.

ted upon or projects more than 24 inches above the pal support for the sign is on the roof, wall or any

on or the transmission of television or other electric ad from a satellite. It may be a solid, open mesh, or shallow dish or parabola.

ed by these regulations to be provided from the line of the plot on which the building is located.

to mitigate the strong winds from the South-West

of Oman, to monitor and regulate Al Duqm

rojected, that: (1) conveys a message or image ention of the public. Some examples of "signs" are f the preceding sentence and that are commonly posters, billboards, murals, diagrams, banners, flags, When not qualified with the terms "on-premise" or signs, whether on or off premise in nature.

n the surface of any floor and the surface of the ove, the space between the floor and the ceiling next vill be counted as a story when more than one-half

street, right-of-way or other shared access way elling but does not include an access leg to a single

so plot Frontage).

mporarily and not permanently mounted to a round.

or building thereon, is designed, arranged or intained. Unless otherwise expressly indicated, the

v enclosed or partially enclosed structure and that es including parking (accessory or non-accessory); hicles; gasoline stations; car washes; motor vehicle and drives; and access drives and driveways.

nagery of television quality or higher.

ilding or other structure or a sign consisting of light e. Wall signs do not include signs that are attached

oduct display window or other window or glazed





08 PREFACE

PURPOSE

The purpose of this document is to provide developers and future plot owners' in Duqm Northern and Central Industrial zones with clear planning framework, design guidelines and plot regulations.

This document provides a simple and straightforward summary of the design guidelines, development control regulations and planning requirements to be followed in the Duqm Industrial Zones.

HOW, WHY & WHO

How to use this document?

The document provides straightforward information to guide the development of Duqm Northern, Central and Southern Industrial zones supported by illustrative charts, diagrams and the different development guidelines adopted by the Duqm Special Economic Zone Authority (SEZAD).

Why is this document needed?

This handbook will provide answers to many plot owners/developers' questions and queries. It will also establish a set of rules and urban guidelines that will ensure creating well designed spaces with integrated building forms and characters.

Who should use this document?

This handbook is essential for plot owners of industrial plots and future developers of Duqm Northern and Central Industrial zones. It is also beneficial for consultants, designers and engineers commissioned by plot owners/developers to perform design/construction services for industrial plots, however, Plot Sheets should be referred to for specific plot guidelines.

DOCUMENT STRUCTURE

This document is broken into the following sections:

- 1. Preamble
- 2. Introduction
- 3. Duqm Master plan
- 4. Light Industry Regulation
- 5. Medium Industry Regulation
- 6. Heavy Industry Regulation
- 7. Renewable Energy Industry Regulations
- 8. General Architectural Guidelines
- 9. Utility Regulations
- 10. Environmental Regulations









10 DUQM INDUSTRIAL PROJECT

PROJECT DESCRIPTION

As part of the new industrial port city at Duqm, SEZAD is developing a substantial industrial zone featuring a wide array of industries and logistical uses.

The Duqm Industrial Master plan project is a significant element of national and economic development for the Sultanate of Oman. The development of the Industrial master plan and the Port of Duqm should enhance and significantly improve the capacity of exports of petrochemicals, minerals, and key manufactured goods, which will act to benefit the Omani people.

The subject land is known as Northern, Central and Southern Industrial Zones of Duqm and is shaped like a right-angled triangle located to the north and west of the port of Duqm, inland to the north-west of the existing airport. It is predominately desert landscape with very sparse areas of plants and trees, and is traversed by a series of large wadis, or natural water channels. The proposed area for development is approximately 244 square kilometres.

The project boundary covers the central and northern parts of Duqm industrial area masterplan. The area includes the main highway, internal roads, train route and other facilities that support the industrial area. Currently it is estimated that the public facilities will be a total of 10% of the area (this will be confirmed when further information is available). The industrial area will be considered as 244 km² (inclusive of the 10% public facilities area).

Figure 1 Project Boundary

DUQM INDUSTRIAL PROJECT

SEZAD VISION

The following is the vision for the Special Economic Zone at Duqm:

To create a bustling activity zone featuring a wide spectrum of economic activities that have an economic appeal; an attractive business and investment core; an efficient industrial hub for heavy, medium and light industries; an integrated model of economic development; and creates a sustainable economic industrial park

SEZAD OBJECTIVES

The objectives for the Special Economic Zone at Duqm are as follows:

- To facilitate the establishment of a diverse range of industries within the industrial clusters;
- To ensure orderly, economical and beneficial use and development of industrial land;
- To maintain and improve the quality of the built environment;
- To ensure development decisions, now and in the future, reflect the values and needs, wants and desires of the SEZAD and reduce the likelihood of land use conflicts;
- To preserve the natural environment and to reduces and/or mitigates impacts associated with industrial development.

The AI Duqm Industrial Master plan Design Guidelines have been prepared to guide development to achieve the SEZAD Vision and achieve the specified objectives.

12

DUQM SPECIAL ECONOMIC ZONE AUTHORITY

SEZAD VISION

Inspired to create a world reknowned industrial hub, the Special Economic Zone Authority Duqm (SEZAD) vision for Duqm Industrial City can be summarized by the following:

- A bustling activity zone featuring a wide spectrum of economic activities
- An appealing economic hub
- An attractive business and investment core
- An efficient industrial hub for heavy, medium and light industries
- An integrated model of economic development
- A sustainable economic industrial park

SEZAD

Established by a Royal Decree in 2011, the Duqm Special Economic Zone Authority (SEZAD) is the sole government entity responsible for managing the economic zone. Fundamentally, SEZAD will run, regulate, manage and oversee all economic activities and operations within the Special Economic Zone and will be referred to as the "Authority" in this document.

Furthermore, the role of SEZAD expands beyond the daily complex operations of the economic zone to provide insightful strategic planning for the development of the modern Duqm City. Committed to creating livable spaces, establishing an economically efficient hub and protecting the environment, SEZAD envisions Duqm City to become a popular regional destination offering residential, recreational and investment opportunities.

Under the wise supervision of SEZAD, the Special Economic Zone is set to develop into an attractive business hub, with a wide-ranging economic center and advanced industrial sector appealing to many investors through offering great incentives, simple business transactions and one-stop shop dealings.

DUQM INDUSTRIAL IDENTITY

DEVELOPMENT CONTROL REGULATIONS INTENT

The Duqm Development Regulations are intended to create a well-integrated industrial development with a unified and synchronized urban form to achieve the desirable business image, the bustling industrial vibe and the appealing investment environment sought by SEZAD. Creating an urban identity compatible with the operational nature of the Duqm industrial site and realizing a well-coordinated business environment are the ultimate goals behind these development regulations.

DISCLAIMER

The development control regulations provided within this document provide minimum regulations and shall not be considered as a substitute for internationally accepted codes and standards. Future plot owners, developers and consultants shall refer to internationally recognized building codes, fire, life and safety codes, environmental codes and disability codes.

2. DUQM MASTERPLAN

15 DUQM INDUSTRIAL MASTERPLAN

LAND USE PLAN

LAND USE BREAKDOWN

Following the feasibility study and the current Duqm Industrial Area Masterplan, Table 1 below summarizes the areas of the various land uses within the project boundary:

PHASE	HEAVY INDUSTRY	MEDIUM INDUSTRY	LIGHT INDUSTRY	SABKHA MED. INDUSTRY	RENEWABLE ENERGY IND.	RAILWAY YARD	UTILITIES HUB	Total Area (km²)
PHASE-1	15.267	8.326	3.710	-	-	-	-	27.303
PHASE-2	24.366	2.189	6.349	2.770	2.232	10.576	2.001	50.483
PHASE-3	-	20.252	5.365	-	-	-	-	25.617
PHASE-4	14.333	13.359	1.328	-	-	-	-	29.020
Total Area (km²)	53.966	41.354	16.752	2.770	5.004	10.576	2.001	132.423

TABLE 1 Area by Land Use and Phase

18 overview

DEFINITION

Light Industry is defined as a zone accommodating a range of light industrial, storage and warehouse land uses which do not create any appreciable nuisance or generate heavy traffic. Light Industry is also more consumer-oriented than business-oriented, since most products are aimed for end use rather than for other industrial uses. The activity and function of the Light Industry typically produce items that are higher in value per unit weight than that of Heavy or Medium Industry.

The requirement for area, the usage of power and the supply and types of raw materials are lesser in Light Industry than in Medium and Heavy Industry.

Clothes, shoes, furniture, consumer electronics and home appliances are examples of Light Industry outputs.

Generally, facilities associated with Light Industry have less of an environmental impact than those associated with Medium and Heavy Industry, hence, are more likely to be zoned closer to residential areas than Medium or Heavy Industries tend. Light Industries are mostly known to have temporary and localized environmental impacts.

19 **PERMITTED USES**

PERMITTED USE

WAREHOUSING • Truck storage

- Warehousing Construction storage yard Electronic storage center
- Vehicular storage and towing

AGRIBUSINESS

- Food processing • Trade of agricultural goods
- and farm inputs Offices related to agribusiness
- Wholesale and trade of
- processed food

MANUFACTURING

- Shoe manufacturing
- Building materials sales
- Cable and wire manufacturing
- Electronic assembly
- Glass cutting and glazing
- Heavy equipment sales and rental
- Jewelry manufacturing
- Laundry facilities
- Light machinery manufacturing
- Machine shops
- Medical and pharmaceutical laboratories
- Metal stamping and extrusion

Optical goods manufacturing

- Package manufacturing
- Pottery and ceramic
- manufacturing
- Printing and publishing Scientific and precision
- instrument production
- Sheet metal shops
- Sign painting
- Stone cutting and grinding
- Tool and die shops
- Woodworking and furniture manufacturing

LOGISTICS

- Intermodel freight transport facilities
- Offices related to industrial uses Weigh stations
- Accessory uses

OTHER

- Bakery
- Catering establishments
- High technology office
- Light equipment sales and rental Offices related to light industrial uses
- Recycling facilities
- Research facilities
- Accessory uses

LIGHT INDUSTRY AREA

Industries and industrial activity is not only the major function, but also, the most prominent in the entire Light Industrial zone. However, other activities and functions such as warehouses, commercial uses, office buildings, retail and community facilities providing service to the entire district may also be located within the Light Industrial Zone. Hence, design guidelines will be provided for all components.

The main land uses within the area zoned as Light Industry:

- 1- Industries
- 2- Warehousing and logistics
- 3- Ancillary uses

20 LAND USE PLAN

The land use plan (Figure 2) indicates the zone designated for the Light Industrial Area. The total area reserved is estimated to be 16.75 km², with the largest area concentrated in the far south and the south east of the industrial area while smaller Light Industry zones are scattered throughout the entire industrial development area.

In addition to Light Industrial functions, the Light Industrial Zone covers supporting and ancillary functions, such as office buildings, retail functions, community facilities, warehouses and logistics, which are required to be provided throughout all zones within the Industrial Area, hence the scattering of smaller Light Industrial Zones.

Figure 2 Light Industry

21 DEVELOPMENT STATISTICS

The Design Statistics section is yet to be completed as it is reliant on information from the final plot sheets. Much of the information that would be contained in the Design Statistics section is included in the overall Design Guidelines. SEZAD to determine whether to include the Design Statistics section in the final Design Guidelines document.

22 DESIGN GUIDELINES

PLOT ENVELOPE

ACCESS AND CIRCULATION

Vehicle Access:

The location of ingress and egress points for vehicles to and from the plots, the circulation within the plot and the implications of these on public traffic are considered while setting the access and circulation design guidelines. The following parameters shall be followed for car and truck access and circulation within the plot in the Light Industrial Zone:

- Where applicable, access to all plots shall only be from an internal street within a Super Block
- Accesses points and internal roads within each plot shall be paved with hard surfaced material that will sustain heavy vehicle movements
- All buildings on the plots, including all building components, shall be accessible by civil defense and fire department vehicles
- Vehicle driveways within the plot shall be located so as to minimize conflict with pedestrian circulation. Minimum width for one way driveways shall be 4m or 7.3m for two way, while parking ramps and egress and ingress points shall be determined taking into consideration the type of trucks and vehicles required to service the nature of industry on each specific plot given that approvals are granted by SEZAD for the dimensions of these access points
- Ornamental entrance structures, pylons and gateways for vehicle driveways are permitted on plots
- Vehicle driveways shall be located a minimum of 2.0m from fire hydrants, a minimum of 1.0m from street lights and adjacent plot lines while egress and ingress points to be located away from street intersections
- Exits and entrances to the plots shall be adequately provided so as not to create congestion at the entry point or generate queuing or safety issues at public roads. Location of the exits and entrances to the plots are shown in plot sheets and shall be followed
- Truck access and circulation within the plot shall be separated from the passenger car access and circulation
- The minimum lane width is 3.65m with a minimum radii of 10m

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

Pedestrian Access:

Pedestrian access points, safety and relationship to the vehicle circulation and the buildings within the plot are considered while scripting the design guidelines so that the vision of a specially designated, clearly defined and well connected pedestrian network is achieved. The following parameters shall be followed for pedestrian circulation within the plots in the Light Industrial Zone:

- Paving material and dimensions of primary pedestrian connections shall differ from those of secondary pedestrian connections
- Pedestrian entrances to buildings shall be clearly defined, visibly marked and easily accessed
- Minimum width of the sidewalk shall be 1.5m in all ROWs and 1.2m within plots.
- Pedestrian connections and walkways shall be safely buffered and protected from vehicular traffic and circulation on plot
- A pedestrian connection shall continuously run from the public pedestrian sidewalk through the parking area pedestrian walkways to the main building pedestrian entrances
- Bicycle racks, if provided, shall be located close to main building pedestrian entrances, however need to be placed so as not to hamper pedestrian traffic

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

23**SETBACKS**

SETBACKS

Setbacks are specified distances required between the plot boundary and the external face of a building or boundary wall. The purpose of setbacks is to provide privacy for the individual plot owners and provide room for emergency vehicle access. Below are requirements to be followed for the Light Industrial Area plots:

- The setbacks for back to back plots in the Light Industrial Zone with a 30m ROW along the front boundary are shown in the graphic above and in Figure 3
 - The front setback shall be equal to 6m and shall incorporate a 1.5m landscape buffer
 - The side setback shall be equal to 3m
 - The rear setback shall be equal to 4m
- ٠ The setbacks for plots in the Light Industrial Zone with a 50m ROW along the rear boundary are shown in the graphic above and in Figure 4
 - The front setback shall be equal to 6m and shall incorporate a 1.5m landscape buffer
 - The side setback shall be equal to 3m
 - The rear setback shall be equal to 7.5m and shall incorporate a 3m landscape buffer
- The setbacks for plots in the Light Industrial Zone with a 80m ROW along the rear boundary ٠ are shown in the graphic above and in Figure 5
 - The front setback shall be equal to 6m and shall incorporate a 1.5m landscape buffer
 - The side setback shall be equal to 3m
 - The rear setback shall be equal to 10m and shall incorporate a 3m landscape buffer
- The green buffer is the section of the setback area closest to the plot boundary where only ٠ trees may be planted and landscaping applied. On plot storm water drainage strategies that utilize landscape areas, these may be adopted and applied to the buffer section
- ٠ The green buffer area along the 30m, 50m, and 80m Right of Way must commence at the plot boundary and continue into the plot
- ٠ In case of corner plots (Figure 6) the setbacks shall be applicable on both the sides as per the street hierarchy. Landscape buffer shall also need to be provided on both the edges fronting the road.

Figure 6 Setback dimensions for corner plots

- Figure 4 Setback dimensions for plot with 50m ROW
- are shown in the graphic above and Figure 6

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

Justifiable setback variations may include:

- ٠ constructed
- plot

The setbacks for corner plots in the Heavy Industrial Zone with a 30m ROW and 100m ROW

All setbacks are to follow respective ROW setbacks in previous figures

Additional landscaping planted to screen development from the street

A landmark architectural development that addresses the street is to be

Parking and major industrial activities are to be located to the rear of the

· Parking is to located below ground or at ground level with G+1 above

Figure 9 Plot on 30m ROW with 80m ROW in the back

26 PLOT COVERAGE

PLOT COVERAGE

Building area is not to exceed **60%** of the Plot Area

Plot coverage is the maximum percentage of the plot area permitted to be covered by buildings or structures and is applied to ensure that the built environment within the area is not compromised. The following clarifies the purpose of plot coverage and its value within the area:

- Plot coverage guarantees that no structure abuts the boundary of the plot for lighting, fire prevention and ventilation purposes
- Plot coverage percentage contributes to increasing the height of buildings by limiting the single floor area in order to achieve an appealing urban environment
- Plot coverage percentage is enforced and applied in order to allow for space within the plot for car and truck entering, circulating, loading, parking and exiting
- Plot coverage shall allow for open space, landscaped areas and green buffers as required on plots
- Plot coverage shall allow for civil defense vehicles to enter and access all parts of all structures built on the plots
- Plot coverage for plots within the Light Industrial Zone is not to exceed 60% of the plot area
- The percentage mentioned above includes all buildings within the plot boundaries. Examples include: electrical rooms, substations, guard and storage facilities as well as any light ancillary buildings that may be located within the premises

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

Figure 10 Plot Coverage Representation for Medium Industry

27 FAR (FLOOR AREA RATIO)

FLOOR AREA RATIO

The Floor Area Ratio directs the intensity of usage and construction on a specific plot. It is related to the volume of all principal built structures on the plot, the plot coverage percentage, the number of floors and the GFA. The Floor Area Ratio is the total area of all floors divided by the total area of the plot.

- ٠ The purpose behind applying an FAR is to ensure that the land is optimally utilized while still enabling an attractive built environment to be developed
- The FAR for plots in the Light Industrial Zone is equal to 0.60 ٠

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

of Floors = 1

of Floors = 2

Floors = 3

28 BUILDING HEIGHT

BUILDING HEIGHT

The building height within the Light Industrial Area is to follow the guidelines below in order to create a harmonious, well balanced urban fabric that conveys the character and the vision of the area:

- The total building height allowed on plots located within the Light Industrial Zone is equal to 3 floors measuring a maximum sum of 18m in height
- For specific operational necessities that require exceeding the set height limit, an exception may be made subject to approval. Building heights equal to 50% of the building setback from the property boundary may be filed for approval
- Examples on structures that may be exempt from height limit (upon approval) are chimneys and wind towers
- It is encouraged to express the excess height of the exempt elements in a creative architectural style that would enrich and enhance the character of the area rather than attempting to conceal it
- The ground floor of light industrial development may be raised by 1.2m (maximum) for loading and unloading purposes. The loading docks can be covered but should not be closed on the sides as we do not want this to appear like a building.
- The maximum height for industrial development shall also be 18m. However, the maximum height of each floor shall correspond to the production requirements along with the dimensions of the machinery and the end product.
- Minimum floor to floor height 3.2m with a maximum height of 5.6m for administration buildings

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

Figure 14 Maximum Building Height for Light Industrial

HT

PLOT AMALGAMATION

In cases where investors are willing to amalgamate 2 or more plots within the Light Industrial Zone, the following shall be taken into consideration:

- All Light Industrial Zone guidelines shall apply to the amalgamated plots
- ٠ The resulting plot shall maintain all external setbacks of the amalgamated boundary so as to preserve the character of the area
- The total GFA allocated for the amalgamated plot shall not exceed the sum GFA of all plots separately
- ٠ Accesses and connections to the amalgamated plot shall be based on the approved connections and entrances for the separate plots
- The amalgamation request is subject to the approval of SEZAD ٠

PLOT SUBDIVISION

following shall be taken into consideration:

- All Light Industrial Zone guidelines shall apply to the subdivided plot ٠
- vehicle accessibility
- on 0.6 FAR
- ٠ connections and entrances plan
- ٠ 25mX50m
- The subdivision request is subject to the approval of SEZAD

Figure 16 Plot Subdivision

Figure 15 Plot Amalgamation

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

In cases where investors are willing to subdivide a plot within the Light Industrial Zone, the

The resulting plot shall maintain all external setbacks of the new boundary as well as additional setbacks from neighboring plots so as to preserve the character of the area and provide sufficient space within the plot for vehicle entrance, circulation and civil defense

The total GFA allocated for the subdivided plot shall not exceed the maximum GFA based

Accesses and connections to the subdivided plots shall be based on the approved

The resulting plot shall not be less than 1,250m² in area with dimensions not less than

30 PARKING REQUIREMENTS

Plot parking for vehicles within the entire industrial area is to be provided either within enclosed buildings or on designated areas. Parking shall be consistent with the parking standards and requirements and shall follow the quidelines below:

- On street parking is provided for cars only
- All parking areas are to be at least 1.5m setback from ٠ the edge of any building, so as to allow for open space, walkways and overhangs
- Car parking and circulation shall be separate from truck ٠ parking and circulation
- Plot access and distance from junctions shall be designed in agreement with SEZAD highway design standards taking into account visibility and other safety issues
- No parking spaces shall be located near natural ventilation or air intake on the plot
- It is recommended to locate the primary parking area to the side or the rear of the plot
- If the plot is located on more than one road, the access to the plot shall be provided from the minor road (30m ROW) maintaining that all accesses shall be from within the super block
- One tree for every six parking bays shall be provided within the parking areas to provide shade
- Parking areas shall be screened from the public view
- Entrances and exits to and from parking and loading facilities shall be appropriately marked with clear directional signs
- If community facility plots have more than one road frontage, then vehicular and pedestrian access shall be provided from each road
- Disabled Parking Bays to be located to the closest point of access to the main administration building via the car park at a rate of 1 bay for every 25 standard bays
- For truck parking requirements, it is the responsibility of the ٠ developer to provide what they need and for the Authority to review and approve
- Ramps must comply with Oman Highway Design

Figure 18 Discouraged front parking location sample

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

Exemptions/reductions in parking may be considered if:

- Premises are to be semi or fully automated and therefore will have a reduced number of employees
- ٠ Employees are transferred to and from the site via communal transport vehicles such as buses

31 PARKING REQUIREMENTS

Figure 20 Standards for different types of parking

32 LOADING/UNLOADING

- In order to avoid traffic congestion in between buildings and to achieve a smooth circulation system within the plot, loading docks and facilities shall be located at the rear of the building and not the front or the sides
- Loading areas shall be screened from public view
- Loading areas shall be offset from vehicle driveways into the plot
- Loading areas are to be designed to accommodate the maximum sized vehicle that will utilize the facility
- Loading areas shall provide sufficient internal turning space to enable vehicles to exit the plot in forward gear
- Vehicles shall enter and exit the plot in forward gear
- Maximum height to raised loading bay is 1.2m

33 BOUNDARY WALLS

BOUNDARY WALLS

Boundary walls serve several purposes within industrial areas; they act as screening to loading/unloading areas, vehicles and utility functions on the plot while also acting as a security element where needed.

- Boundary walls shall surround all plots within the Light Industrial Zone
- Boundary wall structure and foundation to reamin within the respective plots
- Walls are to be of a solid material on the sides and the rear of the plots while a 2m wrought iron simple linear element in black matt finish shall be installed along the frontage of the plot on top of a 1m solid wall base
- The minimum height of a perimeter wall is 3m
- The maximum height of a perimeter wall is 4.5m
- For the frontage of the plots, the solid bottom of the perimeter wall is 1m high while the remainder is reserved for open fencing
- The use of barbed wire fencing is prohibited
- Boundary walls shall be constructed out of durable materials that reflect the architectural character of the area and complement the surrounding walls, buildings and structures
- In case of expanses of boundary walls longer than 30m, articulation and architectural elements shall be applied in order to prevent monotony

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

A landowner can only build boundary walls on their own property, unless an agreement is reached with an adjoining landowner. Landowners are encouraged to prevent two walls being built adjoining each other and thus are recommended to agree to a cost sharing agreement with neighbors and build half on each other's land. If an adjoining landowner is not available then the first owner is required to build a boundary wall on their own land.

34 LANDSCAPING

LANDSCAPE

A specific percentage of each plot within the Industrial Area is to be allocated for landscaping for the purpose of providing a visual amenity that will contribute to the environmental quality and lend a unified and embracing character to the area. In order to achieve this, the following shall be undertaken:

- A minimum of 10% of the plot area shall be reserved for landscaping
- Planting materials shall consist of native or 'adapted to the local climate' species
- Turf areas shall be limited to 10% of the total on plot landscaped area
- Sustainable irrigation methods and technologies such as drip irrigation, moisture sensors and centralized programming and monitoring shall be considered for all planting areas
- A minimum of 25% of the total setback area facing the 30m ROW is to be soft landscape plantings (trees, shrubs, and groundcovers)
- A minimum of 25% of the total setback area facing the 50m ROW is to be soft landscape plantings (trees, shrubs, and groundcovers)
- A minimum of 25% of the total setback area facing the 80m ROW is to be soft landscape plantings (trees, shrubs, and groundcovers)
- Should retention ponds be required, a design that complements the landscaping theme shall be adopted
- The design of the landscape shall take into consideration the type of areas to be landscaped by providing visual appeal to key areas (e.g. entrances, walkways) while aiming to use cost effective design solutions to secondary areas (e.g. loading area)
- Shade trees shall be incorporated within vehicle parking areas to provide shade and visual appeal at a rate of one tree for every six bays minimum
- Shade trees shall be incorporated into buffer areas, close to the street in order to contribute to creating a harmonious and appealing streetscape while also providing shade to pedestrians

STORMWATER MANAGEMENT AND DRAINAGE

Plot owners are responsible for storm water management. An on site strategy shall be adopted for retaining and managing stormwater for reuse in buildings or for landscaping purposes.

Exemptions or slight deviations will only be allowed on a case by case basis depending on specific operational requirements and certain special requirements due to new business and technology. Cases as such have to be approved and permitted by the assessing authorities.

101 UTILITY SERVICES

SITE DRAINAGE AND RUNOFF

Any development or changing of grades within a plot is subject to obtain a DRAINAGE CONNECTION PERMIT from SEZAD. This will be obtained from SEZAD by submitting a Drainage Management Plan to SEZAD.

The developer must demonstrate in this Drainage Management Plan that there is no increase of run-off discharge to SEZAD's right of way from the proposed development or improvements. Therefore, the allowable discharge from the Developer's plot is based on the approach known as pre-development versus post-development.

102 SITE POWER

All applications for power should be made direct to SEZAD.

The Developer shall follow the Oman Electrical Standards available via the Authority of Electricity Regulation (AER) of Oman. All design documents should be submitted formally for approval to the service providers RAECO (Rural Areas Electrical Company) for power arrangements up to 33KV, or OETC (Oman Power Transmission Company) for power requirements of 132KV and above.

Each leased site will be provided with a terminal point by the relevant local service provider. Where applicable, provision of an appropriate gated reserved area within the Customer's plot boundary is required for locating the terminal point. The enclosure or the substation shall be recessed into and alongside of the property and its exact size and location shall be finalized by the local service provider.

Customers are required to provide their own Primary Substation depending upon their demand requirement, as per the table below. The voltage rating, major equipment, and layout of the Substation shall be further coordinated and approved by the relevant service provider.

Load	Voltage Rating	Provider
30MW and above	220/132KV or 132/33KV	OETC
Below 30 MW	132/11KV or 33/11KV	RAECO

Electrical Supply will be provided at various voltage ratings depending on the loads. The voltage range will be ex: - 220KV, 132KV, 33KV, 11KV, 433 Volts and the Frequency will be at 50Hz. The voltage ratings will be at the discretion of the local service provider.

Tariff metering and the isolation facility will form part of the terminal point equipment and the access for these facilities will be strictly at the control of local service provider.

The Customer will be responsible for terminating all cables for power take off at the terminal locations. The developer is responsible for all the electrical works with in their property including statutory fee.

The developers will be provided with only one power connection per lease agreement unless approval granted by SEZAD, in coordination with the service provider.

Power demands more than 1000KVA are generally provided only through a dedicated 11KV feeder Loop in Loop out (LILO). However, special arrangements for the provision of dedicated feeders may be provided if agreed with local service provider in advance.

103 SITE POTABLE WATER SUPPLY

All applications for water connections should be made direct to SEZAD.

The Developer shall follow the PAEW (Public Authority for Electricity and Water) Design Standards. All design documents should be submitted formally for approval to the PAEW.

Each leased site shall be connected to the public potable supply network, unless an alternative proposal for water supply is presented to, and approved by SEZAD.

The Developer shall provide on site potable storage tanks sufficient to provide a minimum of twenty four hours supply. These tanks must be able to provide two hours coverage in the event of fire, and support the daily domestic demand of the plot. These tanks shall be located such that it can supply plot by gravity, and away from daily operations or potential sources of contamination.

The Developer will be responsible for implementing a compliant fire protection system for their plot, in accordance with the relevant design guidelines from the Directorate General of Civil Defense within the Royal Oman Police

All applications for sewerage connections should be made direct SEZAD.

The Developer shall follow the Haya Water's 'Wastewater Design Manual' for all site design and installations. All design documents shall be submitted formally for approval to SEZAD.

Industrial wastewater should be treated and reused on the plot where possible. Any residual wastewater must be treated to the quality parameters outlined in the next table:

No form of waste/water, treated or untreated, is to be discharged to the local storm water network.

Site sewerage storage and network infrastructure must be of durable and impermeable materials. Storage tanks should be adequately vented.

Component	Units	Maximum Limits
pH	-	6 - 10
Colour	-	Raises no objection
B.O.D. (5 days $(a, 20^{\circ}C)$	mg/L	1000
Chemical oxygen demand (COD)	mg/L	1500
Temperature	°C	43
Suspended solids (SS)	mg/L	1000
Total dissolved solids (TDS)	mg/L	3000
Grease and Oil	mg/L	30
Sulphate (as SO ₄)	mg/L	500
Sulphide (total as S)	mg/L	3
Phenols (total)	mg/L	5
Cyanide	mg/L	1
Detergents	mg/L	30
Toxic metals	mg/L	10
Aluminium (as Al)	mg/L	10
Arsenic (as As)	mg/L	1
Barium (as Ba)	mg/L	10
Beryllium (as Be)	mg/L	5
Cadmium (as Cd)	mg/L	2
Chromium (total as Cr)	mg/L	2
Copper (as Cu)	mg/L	1
Iron (total as Fe)	mg/L	5
Lead (as Pb)	mg/L	2
Mercury (as Hg)	mg/L	0.1
Nickel (as Ni)	mg/L	2
Silver	mg/L	0.1
Zinc (as Zn)	mg/L	2
Calcium Carbide	mg/L	Not seen
Radioactive substance	mg/L	Not seen
Yeast, sugar, raw tar, crude oil	mg/L	Not seen
Hydrogen sulphide and polysulphides	mg/L	Not seen
Petroleum spirit, flammable solvent or volatile noxious	mg/L	Not seen
solvents, gases and solids		
Unpolluted water (including condensation, cooling water	mg/L	Not seen
and water drained from roof top)		
Insecticides, herbicides, pesticides, fungicides	mg/L	Imperceptible
Any material that may render wastewater harmful or makes	mg/L	Imperceptible
formal treatment of such waste difficult		

105 SITE TELECOMMUNICATIONS

All applications for telecommunication connections shall be made direct to SEZAD.

The Developer shall ensure all design and installations are to the local service providers' standards. Local service providers are Ooredoo and Omantel.

Al Duqm Industrial Area Design Guidelines

19-01-2017

